

Postfix

Installer les paquets indispensables :

```
apt install mailutils postfix libsasl2-modules
```

/etc/mailname

Rentrer le nom du domaine concerné par l'envoi des mails :

```
free.fr
```

/etc/postfix/main.cf

```
myhostname = web
alias_maps = hash:/etc/aliases
alias_database = hash:/etc/aliases
#REECRITURE MAIL
sender_canonical_maps = hash:/etc/postfix/sender_canonical
#REECRITURE MAIL
myorigin = /etc/mailname
mydestination = hostname, localhost.localdomain, localhost
mynetworks = 127.0.0.0/8 [::ffff:127.0.0.0]/104 [::1]/128
#
relayhost = [smtp.free.fr]:587
smtp_sasl_auth_enable = yes
smtp_sasl_password_maps = hash:/etc/postfix/sasl_passwd
smtp_sasl_security_options = noanonymous
#
mailbox_size_limit = 0
recipient_delimiter = +
inet_interfaces = loopback-only
inet_protocols = ipv4
maillog_file = /var/log/mail.log
```

/etc/aliases

```
# See man 5 aliases for format
postmaster:    root
root:          adm.trivaco@free.fr
```

Prise en compte du fichier modifié :

newaliases

/etc/postfix/sasl_passwd

```
[smtp.free.fr]:587 exemple@domain.fr:@*expasswd!
```

Prise en compte du fichier modifié :

```
postmap /etc/postfix/sasl_passwd
```

/etc/postfix/sender_canonical

root@web	adm.trivaco@free.fr
root@web.localdomain	adm.trivaco@free.fr
www-data@free.fr	adm.trivaco@free.fr
www-data@web	adm.trivaco@free.fr
www-data@web.localdomain	adm.trivaco@free.fr

Prise en compte du fichier modifié :

```
postmap /etc/postfix/sender_canonical
```

Test envoi mail

```
echo "Contenu du mail - bla bla bla" | mail -s "Sujet du mail" exemple@domain.fr
```

From:
<https://memo.trivaco.fr/> - Memo

Permanent link:
<https://memo.trivaco.fr/doku.php?id=postfix&rev=1772870763>

Last update: 2026/03/07 08:06

